



NO.	PART NAME	MATERIAL
1	VENT VALVE	GLASS-FILLED PPL
2	COVER	GLASS-FILLED PPL
3	BODY	GLASS-FILLED PPL
4	BASKET	GLASS-FILLED PPL
5	DRAIN PLUG	GLASS-FILLED PPL
6	PLUG	GLASS-FILLED PPL
* 7	O-RING	VITON
8	BAG RETAINER	GLASS-FILLED PPL
9	O-RING	VITON

* IF REQ'D

NOTES:

- PRESSURE RATING: 150 PSI @ 70° F (NON SHOCK) (10.3 BAR @ 21° C)
MAX. TEMPERATURE RATING: 240°F @ 70 PSI (115°C @ 4.8 BAR)
- VENT GAUGE AND DIFFERENTIAL PRESSURE GAUGE ARE OPTIONAL.
- PIPING CONNECTION (NOM.): 2" NPT (50MM)
DRAIN CONNECTION (NOM.): 2" NPT (50MM)
- BAG SIZES:
BAG #1-SINGLE LENGTH
7" X 16" (2.0 SQ.FT.)
178 MM X 406 MM (1858 SQ.CM.)
BAG #2-DOUBLE LENGTH
7" X 32" (4.1 SQ.FT.)
178 MM X 813 MM (3809 SQ.CM.)
- FOR METAL PIPING INSTALLATION, A MINIMUM OF 20" PLASTIC PIPE IS REQUIRED ON UPSTREAM AND DOWNSTREAM OF FILTER VESSEL.

CERTIFIED FOR:

P.O. NO.:

REG. NO.:

QUOTE NO.:

TAG NO.:

PART NO.	A		B		C		D		E		F		G		H		WT. (DRY)	
	IN.	MM.	IN.	MM.	IN.	MM.	IN.	MM.	IN.	MM.	IN.	MM.	IN.	MM.	IN.	MM.	LBS.	KG.
FLT4201	6.50	165	10	254	3.25	83	34.12	867	20	508	18.38	467	6.13	156	23.88	607	49	22.3
FLT4202	6.50	165	10	254	3.25	83	50.12	1273	36	914	18.38	467	6.13	156	39.88	1013	63	28.6

Monarch Group - Filters, Strainers & Pipeline Equipment
Australia - www.monarchindustrial.com.au
Thailand - www.psfthailand.com

FATON

NAME: POLYLINE BAG FILTER
NPT THREADED CONNECTION
SIZE 2" POLYPROPYLENE

DRAWN: FM DATE: 4/11/95 CERT.: WB DATE: 4/11/95

SIZE: A DWG NO: SD021000 REV: L

UNAUTHORIZED USE, MANUFACTURE OR REPRODUCTION IN WHOLE OR IN PART IS PROHIBITED.

ELECTRONIC FILE NAME: SD021000.DWG

REF. ECR: D817 DATE: 3/22/06