



NO.	PART NAME	MATERIAL
1	BODY	CSTL ASTM A216 GR.WCB
2	SCREEN	
	PERF. DIA. MESH	
3	COVER	CSTL ASTM A216 GR.WCB
4	YOKE	DUCTILE IRON
5	YOKE SCREW	STEEL
6	O-RING	BUNA-N
7	STUD	STEEL
8	DRAIN PLUG	CARBON STEEL
9	BODY PLUG	CARBON STEEL

NOTES:

1. INLET/OUTLET 150 LB. RAISED FACED FLANGED CONNECTIONS PER ANSI B16.5.
2. 5/8" DIAMETER SLOTTED FOOT PADS FOR 8" SIZE.
3. DIMENSION "G" (NPT) IS FOR DRAIN PLUG, ITEM 8.
4. ITEM 9, BODY PLUG IS NOT TO BE USED AS DRAIN.
5. MAX. WORKING PRESSURE: 200 PSI @ 100° F
(13.8 BAR @ 37.8° C)

CUSTOMER:
P. O. NO.:#
REG. NO.:#
QUOTE NO.:#
TAG NO.:#

PIPE SIZE (NOMINAL)	DIMENSIONS									WEIGHT (DRY) LBS. KGS.	PART NO.							
	A		B		C	D		F	G (NOM.)			H	J					
	IN.	MM.	IN.	MM.	IN. MM.	IN.	MM.	IN. MM.	IN. MM.	IN. MM.	IN. MM.							
8" (200mm)	27.00	/ 686	40.00	/1016	15.50	/394	27.00	/ 686	60	/1524	1/2	(15)	15.75	/400	8.63	/219	550/ 249	ST0720800R3C

FATON	Monarch Asia Pacific Pty Ltd Brisbane, Australia +61 (0) 7 3298 5000 www.monarchindustrial.com.au		
	NAME MODEL 72 SIMPLEX STRAINER 150# RAISED FACE FLANGE SIZE 8" CARBON STEEL		
DRAWN FM	DATE 1/25/95	CERT. LF	DATE 1/25/95
SIZE A	DWG NO	SD072029	
			REV C

UNAUTHORIZED USE, MANUFACTURE OR REPRODUCTION IN WHOLE OR IN PART IS PROHIBITED.

ELECTRONIC FILE NAME: SD072029.DWG
REF. ECR 0507 DATE 11/1/05