

Y Strainers

1/2" to 4" - PVC and Corzan® CPVC



Features

- Rated to 150 PSI
- FPM Seals
- Standard 1/32" perf screen
- All-Plastic Construction
- Easy Screen Access
- Can Be Used in Horizontal or Vertical Position

Options

- Stainless Steel Strainer Screens
- True Union Connections Available

Economical Protection

Hayward Y Strainers protect piping system components from damage caused by dirt or debris in the process media. They cost less than other types of strainers and are lightweight and very compact. Because they can often be supported by the pipeline alone, they work in applications where other strainers cannot.

Rugged Plastic Screens

Hayward Y Strainers are supplied with a 1/32" perforated plastic screen. This screen is ultrasonically welded, not glued, for superior strength. Screens fabricated from type 316 stainless steel are also available in openings from 1/2" down to super fine 325 mesh. All screens have an open area at least twice that of the equivalent pipe size cross-sectional area to minimize pressure drop.

Easy Clean Out

All sizes of Hayward Y Strainers feature a heavy-duty hex cap that permits quick and easy removal of the strainer screen when cleanout becomes necessary.


Adaptable Design

Hayward Y Strainers will work equally well in the horizontal or vertical position, simplifying piping system layout.

All Plastic Construction


Hayward Plastic Y Strainers will never rust or corrode – and they don't require painting or coating to survive corrosive environmental conditions.

Technical Information



Parts List Y Strainer

1. Cap
2. O-Ring Seal
3. Screen
4. Body



Dimensions - Inches / Millimeters

Size	A	B	C	D	E	F	G	H	J	K	L	Weight (lb / kg)	
												Sket/Thd	Flg
1/2"	3.38 / 86	1.38 / 35	2.25 / 57	1.50 / 38	N/A	0.56 / 14	1.00 / 25	2.13 / 54	2.50 / 64	2.25 / 57	6.64 / 169	0.25 / .11	N/A
3/4"	4.18 / 106	1.69 / 43	2.88 / 73	2.00 / 51	N/A	0.81 / 21	1.25 / 32	2.75 / 70	3.00 / 76	2.63 / 67	7.42 / 188	0.63 / .29	N/A
1"	5.19 / 132	2.00 / 51	3.63 / 92	2.16 / 55	N/A	1.00 / 25	1.50 / 38	3.30 / 84	3.32 / 84	3.00 / 76	8.97 / 228	0.88 / .40	N/A
1-1/4"	6.63 / 168	2.63 / 67	4.50 / 114	2.94 / 75	N/A	1.25 / 32	2.00 / 51	4.50 / 114	4.45 / 113	4.75 / 120	13.01 / 330	1.75 / .80	N/A
1-1/2"	6.63 / 168	2.63 / 67	4.50 / 114	2.94 / 75	N/A	1.56 / 40	2.00 / 51	4.50 / 114	4.45 / 113	4.75 / 120	12.07 / 307	1.63 / .74	N/A
2"	7.63 / 194	3.38 / 86	5.38 / 137	3.75 / 95	11.00 / 279	2.00 / 51	2.38 / 60	5.06 / 129	4.88 / 124	4.75 / 120	13.05 / 331	3.00 / 1.4	5.00 / 2.3
2-1/2"	10.31 / 262	4.69 / 119	7.25 / 184	5.25 / 133	N/A	2.90 / 74	3.50 / 89	6.60 / 168	6.54 / 166	6.40 / 163	16.77 / 426	7.75 / 3.5	N/A
3"	10.31 / 262	4.69 / 119	7.25 / 184	5.50 / 140	14.37 / 365	2.90 / 74	3.50 / 89	6.60 / 168	6.54 / 166	6.40 / 163	16.77 / 426	7.50 / 3.4	12.25 / 5.7
4"	12.81 / 325	5.75 / 146	8.88 / 226	6.18 / 157	17.73 / 450	3.78 / 96	4.25 / 108	8.00 / 203	8.58 / 218	8.56 / 217	21.23 / 539	9.50 / 4.3	17.50 / 8.0

Cv Factors*

Size	Factor	Size	Factor
1/2"	4.0	2"	28
3/4"	6.8	2-1/2"	40
1"	9.0	3"	65
1-1/4"	12	4"	100
1-1/2"	28		

* With 1/32" plastic screen

Pressure Drop Calculations


The pressure drop across the strainer, for water or fluids with a similar viscosity, can be calculated using the formula at the right:

$$\Delta P = \left[\frac{Q}{Cv} \right]^2$$

Where ΔP = Pressure Drop
 Q = Flow in GPM
 Cv = Flow Coefficient

The pressure loss across a valve or filter can be calculated using the system's flow rate and the Cv factor for that valve or filter. For example, a 1" strainer with a Cv factor of 8 will have a 4 PSI pressure loss in a system with a 16 gpm flow rate $(16 \div 8)^2 = 4$

Operating Temperature/Pressure



Selection Chart

Size	Material	End Connection	Seal	Rating
1/2" to 4"	PVC, CPVC	Thd, Skt, Flg*	FPM	150 PSI @ 70°F

* 1/2" to 1-1/2" not available with flanged connections

Strainer Screen Selection

- Y Strainers are furnished with a 1/32" perf plastic screen.
- Stainless steel strainer screens are available in these perfs: 1/32", 3/64", 1/16", 5/64", 7/64", 1/8", 5/32", 3/16", 1/4", 3/8", 1/2"; and in mesh sizes: 20, 40, 60, 80, 100, 200, 325